

The logo features the word "TUBEX" in a bold, white, sans-serif font with a registered trademark symbol, set against a blue background. The word "FONO" is written in a larger, grey, sans-serif font to the right of "TUBEX".

TUBEX

FONO



TUBEX[®] FONO

Tubex FONO is an insulation pipe with PE coating made of lightweight polyethylene for sound insulation of waste water fittings and rainwater outlets. It is characterised by increased resistance to mechanical stress, flexibility and ease of installation. The lightweight structure of the PE-coated insulation is soft and uniform in sections. FONO insulation is produced in wall thicknesses of 5 mm and 10 mm in blue colour. They are available in standard lengths of 15 m and 10 m.

FONO insulation is used for sound insulation of wastewater fittings and internal rainwater downpipes with increased resistance to mechanical stress.

- Highly durable insulation with increased resistance to mechanical stress
- Easy installation and handling
- Blue colour (red variation)
- Prevents dewetting of the leads
- Excellent sound insulation
- Protects against corrosion
- Prevents wetting of masonry and floor coverings

Technicla parameter	Value	Standard
Reaktion to fire	EL	ČSN EN 13501-A1
Thermal conductivity	≤ 0,040 W/(mK)	ČSN EN ISO 13787
Short-term water absorption	WS 01 (0,08 kg/m ²)	ČSN EN 13472
Water vapour permeability	MU 2000	ČSN EN 13469
Maximum operating temperature	ST(+) 90	ČSN EN 14707

Storage:

Extruded polyethylene materials must be stored in a dry and covered environment and must not be exposed to direct sunlight. .

The production of TUBEX® insulation is certified and meets the requirements of ČSN EN ISO 9001:2015.

DIMENSIONAL RANGE				
Outside diameter (mm)	Inside diameter (mm)	Wall thickness (mm)	Number of rolls per carton	Roll length (m)
40	48 – 55	5	11	15
50	58 – 65	5	9	15
63	70 – 75	5	7	15
75	80 – 90	5	7	15
80	85 – 95	5	7	15
100	115 – 120	5	5	15
110	116 – 130	5	5	15
125	130 – 145	5	4	15